

## PERFORMANCE DATA

Total Solar Energy Rejected (Heat)	44%
Visible Light Transmitted	48%
Visible Light Reflected (External)	13%
Ultra Violet Rejected	98%
Shading Coefficient	0.64
SHGC	0.56
U-Value – (W/m <sup>2</sup> K)	5.68
Glare Reduction	45%
Solar Energy Reflected	12%
Solar Energy Absorbed	40%
Estimated Fade Reduction*	64%
W.E.R.S Star Rating (cooling)	2.0
(heating)	0.5

Applied to 6mm clear glass

\* This data is a guide enabling an estimate only of fade reduction. As there are variables that cause fading, it would be impossible to give an exact figure. The data therefore does not constitute warranty.

## BENEFITS

- W.E.R.S. Rating 2 Stars (cooling)/0.5 (heating).
- Ideal for commercial and residential application.
- Advanced sputtering technology.
- Only stabilised metals used in production.
- Original colour guaranteed to last.
- Rejects 44% of heat.
- Glare reduction.
- Strengthens glass for added safety.
- Over 98% of harmful UV rejected.
- Good fade reduction.
- World's toughest scratch resistant surface.
- Clear distortion free adhesive.
- Lifetime warranty residential - not transferable.
- 12 year warranty commercial - not transferable.

**N1050 NEUTRAL**  
SOLAR CONTROL SERIES

