

PERFORMANCE DATA

Total Solar Energy Rejected (Heat)	28%
Visible Light Transmitted	69%
Visible Light Reflected (External)	20%
Ultra Violet Rejected	>98%
Shading Coefficient SHGC	0.82 0.72
U-Value – (W/m ² K)	6.19
Glare Reduction	22%
Solar Energy Reflected	18%
Solar Energy Absorbed	15%
Estimated Fade Reduction*	55%
W.E.R.S Star Rating (cooling)	-

Applied to 6mm clear glass

* This data is a guide enabling an estimate only of fade reduction. As there are variables that cause fading, it would be impossible to give an exact figure. The data therefore does not constitute warranty.

BENEFITS

- Polyester film.
- Economic alternative to acid etched glass.
- Ideal for logos, lettering & interior design work.
- Can be computer cut.
- Has a soft white appearance internally and externally.
- Stops 28% of heat.
- Gives total privacy day and night.
- Excellent fade reduction.
- Allows most of the light to still come through.
- Strengthens glass for added safety.
- Pressure sensitive adhesive.
- Over 98% of harmful UV reduction.
- Warranty: 5 years internal, 15 years internal non sun facing partitions - not transferable.

NRMPS (2) TRANSLUCENT WHITE
DECORATIVE MATT SERIES

