

PERFORMANCE DATA

Total Solar Energy Rejected (Heat) 73%

Visible Light Transmitted 6%

Visible Light Reflected (External) 13%

Ultra Violet Rejected 98%

Shading Coefficient 0.31
SHGC 0.27

U-Value – (W/m²K) 5.70

Glare Reduction 93%

Solar Energy Reflected 20%

Solar Energy Absorbed 68%

Estimated Fade Reduction* 81%

W.E.R.S Star Rating (cooling) 4

Applied to 6mm clear glass

* This data is a guide enabling an estimate only of fade reduction. As there are variables that cause fading, it would be impossible to give an exact figure. The data therefore does not constitute warranty.

BENEFITS

- W.E.R.S. Rating 4 Stars (cooling).
- Popular for use on commercial buildings with clear glass.
- Gives attractive deep grey appearance externally.
- Stops 73% of heat.
- Helps reduce heat loss in winter.
- Reduces energy costs all year round.
- Designed for areas with severe glare problems. Ideal for computer rooms.
- Excellent daytime privacy.
- Strengthens glass for added safety.
- Over 98% of harmful UV rejected.
- Excellent fade reduction.
- World's toughest scratch resistant coating.
- Clear distortion free adhesive.
- Lifetime warranty residential - not transferable. 12 year warranty residential - not transferable.

NS 10 GREY
SOLAR CONTROL SERIES

