

PERFORMANCE DATA

Total Solar Energy Rejected (Heat) 76%

Visible Light Transmitted 8%

Visible Light Reflected (External) 18%

Ultra Violet Rejected 98%

Shading Coefficient 0.28

SHGC 0.24

U-Value – (W/m²K) 5.22

Glare Reduction 91%

Solar Energy Reflected 34%

Solar Energy Absorbed 57%

Estimated Fade Reduction* 82%

W.E.R.S Star Rating -

Applied to 6mm clear glass

* This data is a guide enabling an estimate only of fade reduction. As there are variables that cause fading, it would be impossible to give an exact figure. The data therefore does not constitute warranty.

BENEFITS

- Popular for use on commercial buildings with clear glass.
- Gives attractive deep bronze appearance externally.
- Stops 76% of heat.
- Helps reduce heat loss in winter.
- Reduces energy costs all year round.
- Designed for areas with severe glare problem. Ideal for computer rooms.
- Excellent daytime privacy.
- Strengthens glass for added safety.
- Over 98% of harmful UV rejected.
- Excellent fade reduction.
- World's toughest scratch resistant surface.
- Clear distortion free adhesive.
- 7 year warranty - not transferable.

R15 BRONZE
SOLAR CONTROL SERIES

